

Termination boxes KL1, KL2



Termination boxes enclose hydrometric cable of submersible level transmitters and the reference atmospheric pressure tube.

	KL 1	KL 2
Number of signal lines	2 (4 – 20 mA)	2 (4 – 20 mA)
Housing	Aluminum	Plastic
Cable gland	M16x1.5, polyamide, Seal — NBR	
Ingress protection rating	IP 66	
Wires cross section	up to 2,5 mm ²	
Clamped cable diameter	5...10 mm	
Weight	550 g	220 g
Options	Temperature converter (for Pt100)	

KL 1 ORDERING CODE

KL 1 100 - 00R	Standard version
KL 1 101 - 00R	Optional: overvoltage protection
KL 1 1T0 - 00R	Optional: built-in temperature converter (for Pt100)
KL 1 1T1 - 00R	Optional: overvoltage protection + temperature converter

KL 2 ORDERING CODE

KL 2 200 - 00R	Standard version
KL 2 201 - 00R	Optional: overvoltage protection
KL 2 2H0 - 00R	Optional: built-in HART interface
KL 2 2H1 - 00R	Optional: overvoltage protection + HART interface

AGP power supply unit



Stabilized power supply units deliver electricity to low-power devices as part of industrial-grade control setups.

	AGP-12-2	AGP-24-1
Type	Pulse	
Rated input voltage	220 V ± 20%	
Number of DC outputs	4, uninsulated	
Rated output voltage	12 V	24 V
Max load current	2 A	1 A
Permissible temperature limits	- 20 ... +60 °C	
DIN bar type	35 x 7,5 mm	
Weight	0,2 kg	